

# MILSIGHT® S140-D ADUNS

Dual-Band I<sup>2</sup> & Thermal Weapon Sight

## APPLICATIONS

**TARGET ACQUISITION**

**RECONNAISSANCE**

**COVERT OPERATIONS**

**SURVEILLANCE**

**SPECIALTY LAW**

**ENFORCEMENT**



Designed to mount on any MIL-STD-1913 rail interface forward of an existing scope, the MilSight® S140-D ADUNS (advanced dual-band universal night sight) offers ultimate mission flexibility. Use as a thermal weapon sight, on a spotting scope for long-range reconnaissance, or as a handheld observation device. The ADUNS system offers high-resolution blended thermal and image intensified night vision that provides crisp imagery through total darkness, fog, smoke, dust, and many other obscurants.

Snipers can choose to view targets in either thermal, I<sup>2</sup>, or blended channels to optimize target detection and recognition. I<sup>2</sup> penetrates glass and provides IFF while thermal circumvents camouflage and provides rapid target detection. Configurable with white and green phosphor tubes for high-performance US and exportable versions. White phosphor provides a natural looking scene while high-resolution 72 lp/mm in either green or white phosphor produces sharper scene details for longer-range target engagements.

## FEATURES

### ADJUSTABLE BLENDING OF IR AND I<sup>2</sup>

High-resolution blended thermal/image-intensified light night weapon sight provides crisp imagery in complete darkness and under foggy, smoky, or dusty conditions.

### BORESIGHT MAINTAINED AFTER WEAPON DISCHARGE

Coaxial design aligns point of aim and point of impact in thermal, I<sup>2</sup>, and blended views for increased target engagement capability and lethality.

### COMPACT, LIGHT, AND RUGGED

Highly portable design reduces operator fatigue and large, rugged controls for basic image adjustments means no complex menus to navigate.

### SHOCK MITIGATION MAINTAINS BORESIGHT

The proprietary Teledyne FLIR Shock Mitigation System™ (SMS™) absorbs and dissipates high shock loads while extending tube life and maintaining zero.

### MISSION FLEXIBILITY

Functions as a thermal weapon sight, a spotting scope for long range reconnaissance, and a handheld night vision observation device.

## SPECIFICATIONS

System Characteristics		SNIPER (S140-D)
Magnification	Unity	
Optimum Dayscope Magnification	4x to 12x	
Focus Range	15 m to Infinity	
Channel-to-Channel Parallax	None at any range	
I2 Field of View	8.8°	
IR Field of View	7.1° H x 5.3° V	
IR IFOV	0.19 mr	
IR Objective	88 mm, f/0.88	
VisNIR Objective	91 mm, f/0.97	
Image Intensifier Gain	75,000 max	
Output Aperture	40 mm	
Boresight Characteristics		
Accuracy	Factory Aligned to 1 MOA or Better	
Repeatability	Within 1 MOA	
Power		
Power requirements	4 each AA Li (L91)	
Dimensions, Weight & Mounting		
Shock Mitigation System™ (SMS™)	Standard Feature	
Interface (to MIL-STD 1913)	Dual Locking Levers	
Dimensions	11.2" (28.5 cm) x 4.6" (11.7 cm) x 4.3" (11 cm)	
Weight (w/o batteries)	4.5 lbs (2.25 kg)	
Center Height Above Rail	1.5" typical	
Interfaces		
Command and Control	On camera and remote pendant	
Video	External video - Thermal	



### AMERICAS

27700 SW Parkway Ave  
Wilsonville, OR 97070

### EUROPE

2 Kings Hill Avenue - Kings Hill  
West Malling, Kent ME19 4AQ  
United Kingdom

Antennv gen 6,  
PO Box 737  
SE-187 66 Täby  
Sweden

### MIDDLE EAST

Wadi Al Fey St.  
Building 60, Office # 302  
New Ministries Exit /  
Khalifa Park Area  
Abu Dhabi, U.A.E.

Office 127, First Floor  
Akaria Plaza Building, Olaya Street  
Riyadh, 11481, Saudi Arabia

### ASIA

Meguro Tokyo Bldg. 5F,  
2-13-17  
Kami-Osaki, Shinagawa-ku.  
Tokyo, 141-0021, Japan

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2021 Teledyne FLIR LLC. All rights reserved.

Revised on 09/06/21  
Milsight S140-D ADUNS\_Datasheet-LTR  
21-0906