



EXFIL® BALLISTIC VISOR

A low-profile, lightweight visor system that mounts quickly and tool-free to the front section of the EXFIL® Rail 3.0.

PERFORMANCE STANDARDS

- MCEP in accordance with MIL-PRF-32432(GL), 9Jan13
- ANSI Z87.1 2010 - Details on Back

ENVIRONMENTAL CONDITIONS / MIL-STD-810G METHODS

- 501.5P1 High Temperature
- 502.5P1 Low Temperature
- 507.5 Humidity
- 509.5 Salt Fog
- 510.5P11 Blowing Sand/Dust
- 514.6 Loose Cargo Vibration
- 500.5P1 Low Pressure (Altitude)

WEIGHT

- Size 1 | 158 g (0.35 lbs)
- Size 2 | 162 g (0.36 lbs)

SIZING / COMPATIBILITY

- Available in size 1 or size 2
- Compatible with EXFIL® Ballistic SL of respective size
- Compatible with EXFIL® Ballistic or EXFIL® Carbon of respective size fitted with an EXFIL® Rail 3.0
- Compatible with EXFIL® LTP fitted with an EXFIL® Rail 3.0; the size 1 visor fits both helmet sizes




PERFORMANCE / COVERAGE

- > Exceeds impact, fragmentation and optical requirements of Military Combat Eye Protection (MCEP) in accordance with MIL-PRF-32432(GL), 9Jan13
- > MCEP requirements include meeting ANSI Z87.1 2010
- > Coverage area of 186.1 cm² (28.9 in²)

MATERIALS

- > Glass-reinforced polycarbonate and nylon frame components
- > Polycarbonate lens by Eye Safety Systems
- > Stainless steel hardware

COLORS

-  Black (FED-STD-595C #37031)
-  Coyote Brown (FED-STD-595C #20150)
-  Ranger Green (Pantone 7770c)



SCAN / CLICK FOR
PART NUMBERS

